

No. 809, Chuhua Branch Road, Fengxian District, Shanghai

# SAFETY DATA SHEET

Version: v1

Revision Date: 2023-12-06

Print Date: 2023-12-08

### SECTION 1:Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : n-Butyl acrylate

Product Number : B100036
Brand : aladdin
CAS-No. : 141-32-2

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances.

## 1.3 Details of the supplier of the safety data sheet

Company : Shanghai Aladdin Biochemical Tech Co.,Ltd

Address : 36 Xinjinqiao Road, Shanghai

Telephone : 400-620-6333
Fax : no data available

## 1.4 Emergency telephone number

Emergency Phone : 0532-83889090

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226

Acute toxicity, Inhalation (Category 4), H332

Acute toxicity, Dermal (Category 4), H312

Skin irritation (Category 2), H315

Eye irritation (Category 2), H319

Skin sensitization (Category 1), H317

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

Long-term (chronic) aquatic hazard (Category 3), H412

### 2.2 GHS Label elements, including precautionary statements



## No. 809, Chuhua Branch Road, Fengxian District, Shanghai

Pictogram			
Signal word	Warning		
Hazard statement(s)			
H226	Flammable liquid and vapor		
H303	May be harmful if swallowed		
H315	Causes skin irritation		
H317	May cause an allergic skin reaction		
H319	Causes serious eye irritation		
H335	May cause respiratory irritation		
H401	Toxic to aquatic life		
H412	Harmful to aquatic life with long lasting effects		
H312+H332	Harmful in contact with skin or if inhaled		
Precautionary statement(s)			
P210	Keep away from heat, hot surface, sparks, open flames and other ignition		
	sources No smoking.		
P233	Keep container tightly closed.		
P240	Ground/bond container and receiving equipment.		
P241	Use explosion-proof [electrical/ventilating/lighting//] equipment.		
P242	Use only non-sparking tools.		
P243	Take precautionary measures against static discharge.		
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.		
P264	Wash hands [and] thoroughly after handling.		
P271	Use only outdoors or in a well-ventilated area.		
P272	Contaminated work clothing should not be allowed out of the workplace.		
P273	Avoid release to the environment.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P312	Call a POISON CENTER or doctor/ if you feel unwell.		
P303+P361+P353	IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower].		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.		
P333+P313	IF SKIN irritation or rash occurs: Get medical advice/attention.		
P337+P313	IF eye irritation persists: Get medical advice/attention.		
P370+P378	In case of fire: Use to extinguish.		
P405	Store locked up.		
P403+P233	Store in a well-ventilated place. Keep container tightly closed.		
P403+P235	Store in a well-ventilated place. Keep cool.		
P501	Dispose of contents/container to an approved waste disposal plant.		
P304+P340+P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing.Call		
. 55111 51511 512			

a POISON CENTER or doctor. if you feel unwell.



No. 809, Chuhua Branch Road, Fengxian District, Shanghai

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Synonyms : Acrylic acid n-butyl ester; Acrylic Acid Butyl Ester

Formula : C7H12O2

Molecular weight : 128.17

CAS No. : 141-32-2

EC-NO. : 205-480-7

		• • •
Component	Classification	Concentration
n-Butyl acrylate		
	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2; Skin Sens. 1; STOT SE	reagent
	3; Aquatic Chronic 3; H226, H332, H312, H315, H319, H317, H335, H412	grade,98%,contains
		50ppm MEHQ as
		stabilizer

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a

physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

## 4.2 Most important symptoms and effects, both acute and delayed

no data available

### 4.3 Indication of any immediate medical attention and special treatment needed

no data available

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media



No. 809, Chuhua Branch Road, Fengxian District, Shanghai

Suitable extinguishing media Carbon dioxide (CO2) Foam Dry powder Unsuitable extinguishing media no data available

## 5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible. Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated temperatures. Development of hazardous combustion gases or vapours possible in the event of fire.

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

### 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

#### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions. Take up with liquid-absorbent material. Dispose of properly. Clean up affected area.

#### 6.4 Reference to other sections

For disposal see section 13.

#### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.Light sensitive

### 7.3 Specific end use(s)

no data available



No. 809, Chuhua Branch Road, Fengxian District, Shanghai

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

### 8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of Regulation (EU)2016/425 and the standard EN 374 derived from it.

**Body Protection** 

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a fullface particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN(EU).

Control of environmental exposure

If safety requires, prevent further leakage or spillage. Do not let the product enter the sewer.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

a) Appearance form: liquid color: colorless

b) Odour no data available c) Odour Threshold no data available d) pH no data available

e) Melting point/freezing point -64°C f) Initial boiling point and boiling range 145°C

g) Flash point 35-40°C , 100.4 °F h) Evaporation rate no data available i) Flammability (solid, gas) no data available



No. 809, Chuhua Branch Road, Fengxian District, Shanghai

j) Upper/lower flammability or

explosive limits no data available k) Vapour pressure no data available l) Vapour density no data available

m) Relative density 0.899

n) Water solubility
o) Partition coefficient: n-octanol/water no data available
p) Auto-ignition temperature
q) Decomposition temperature
r) Viscosity
s) Explosive properties N
no data available
no data available
no data available
no data available

## 9.2 Other safety information

no data available

### **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

#### 10.3 Possibility of hazardous reactions

Risk of explosion with: Amines Strong oxidizing agents polymerisation initiators halogens hydrides Acids and bases Violent polymerization may be caused by: Strong heating.

#### 10.4 Conditions to avoid

Heating.

#### 10.5 Incompatible materials

no data available

### 10.6 Hazardous decomposition products

no data available

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 3.150 mg/kg

(OECD Test Guideline 401)



No. 809, Chuhua Branch Road, Fengxian District, Shanghai

Acute toxicity estimate Inhalation - 4 h - 11,2 mg/l

(Calculation method)

LC50 Inhalation - Rat - male - 4 h - 11,2 mg/l

(OECD Test Guideline 403)

Acute toxicity estimate Dermal - 2.000 mg/kg

(Calculation method)

LD50 Dermal - Rabbit - male - 2.000 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit Result: irritating Remarks: (External MSDS)

Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation Remarks: (External MSDS)

Respiratory or skin sensitisation

Local lymph node assay (LLNA) - Mouse Result: positive (OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test Test system: Salmonella typhimurium Result: negative Remarks: (National Toxicology Program) Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 490 Result: negative Test Type: unscheduled DNA synthesis assay Test system: Other cell types Metabolic activation: without metabolic activation Result: negative Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 490 Result: negative Test Type: Chromosome aberration test Species: Hamster Application Route: inhalation (vapor) Method: OECD Test Guideline 475 Result: negative Test Type: Chromosome aberration test Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 475 Result: negative

Carcinogenicity

no data available

Reproductive toxicity

no data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Additional Information

Assessment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission



No. 809, Chuhua Branch Road, Fengxian District, Shanghai

Regulation (EU) 2018/605 at levels of 0.1% or higher.

Repeated dose toxicity - Rat - male - Oral - 90 d - NOAEL (No observed adverse effect level) - 84 mg/kg Remarks: Subchronic toxicity

Repeated dose toxicity - Rat - male and female - inhalation (vapor) - 90 d - NOAEL (No observed adverse effect level) - 0,11 mg/kg

RTECS: UD3150000 To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated., Cough, Shortness of breath, Headache, Nausea, Vomiting

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Toxicity to fish flow-through test

LC50 - Oncorhynchus mykiss (rainbow trout) - 5,2 mg/l - 96 h (OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

flow-through test EC50 - Daphnia magna (Water flea) - 8,2 mg/l - 48 h

Toxicity to algae

static test EC50 - Pseudokirchneriella subcapitata (green algae) - 5,2 mg/l - 96 h (OECD Test Guideline 201)

Toxicity to bacteria

static test EC0 - activated sludge - > 150 mg/l - 3 d

#### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d Result: 80 - 90 % - Readily biodegradable. (OECD Test Guideline 310)

#### 12.3 Bioaccumulative potential

no data available

#### 12.4 Mobility in soil

no data available

#### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

no data available



No. 809, Chuhua Branch Road, Fengxian District, Shanghai

#### **SECTION 13:**

### 13.1 Disposal considerations

**Product** 

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

## **SECTION 14: Transport information**

DOT (US)

UN number: 2348 Packing group: III Class: 3

Proper shipping name: BUTYL Reportable Quantity(RQ): no data Poison Inhalation Hazard: no data

ACRYLATES, STABILIZED available available

Environmental Hazards: no

**IMDG** 

UN number: 2348 Packing group: III EMS-No: no data available

Proper shipping name: BUTYL ACRYLATES, STABILIZED

IATA

UN number: 2348 Packing group: III Class: 3

Proper shipping name: BUTYL ACRYLATES, STABILIZED

#### **SECTION 15: Regulatory information**

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

#### **SECTION 16: Other information**

Further information

Copyright Aladdin Co. Ltd. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Aladdin Co. Ltd. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

Version: v1 Revision Date: 2023-12-06 Print Date: 2023-12-08